

Fuse plug - PV-C-M/F-PRO/F-1500/15-EU - 1622149

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Fuse connector for protecting modules and devices in photovoltaic systems, black, SUNCLIX pin connector pattern, 1500 V/15 A, IP68 (24 h/2 m)

SUNCLIX fuse connector, in the version for 1500 V system voltage

Product Description

SUNCLIX fuse connector, for 1500 V system voltage, fuse-link nominal current of 15 A, EU version

Why buy this product

- ☑ One-piece design
- ☑ Robust, easy-to-install fuse element for outdoor use
- ☑ Degree of protection: IP68 (24 h/2 m)

 $\overline{\mathbf{v}}$

☑ 1500 V



Key Commercial Data

Packing unit	8 STK
Minimum order quantity	8 STK
GTIN	4 055626 130774
GTIN	4055626130774

Technical data

Ambient conditions

Degree of protection (when plugged in)	IP66 / IP68 (2 m / 24 h)
Ambient temperature (operation)	-40 °C 50 °C

General

Rated voltage	1500 V
Fuse-link nominal current	15 A DC (Nominal current of the fuse-link)
Fuse adapter nominal current	13 A DC



Fuse plug - PV-C-M/F-PRO/F-1500/15-EU - 1622149


Technical data

Material

Flammability rating according to UL 94	V0	
Standards and Regulations		
Flammability rating according to UL 94	V0	
Environmental Product Compliance		
China RoHS	Environmentally friendly use period: unlimited = EFUP-e	
	No hazardous substances above threshold values	

Drawings

Dimensional drawing



Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com